

# ENTRY-LEVEL TRAILERS

## THE ARROW 8.5' WIDE



*Deluxe Model Shown. Trailers shown may feature optional equipment available at an additional charge.*

## SMART FROM THE START!

The American Hauler **ARROW 8.5' WIDE** is a smart move from the get-go. Its functional design provides all the fundamental necessities to tackle a laundry list of "to-do's." The **ARROW** is perfect for those on a budget, but not willing to sacrifice on dependability. The **ARROW** is designed for maximum value and cargo-carrying versatility. Be sure to add the Deluxe Package with 3/8" interior sidewalls, .030 colored exterior, and 5,000 lb. floor mounted D-Ring to get even more value for your investment. A smart choice for sure.

# SPECIFICATIONS

|                                        | AR8516TA2           | AR8520TA2           | AR8524TA2           |
|----------------------------------------|---------------------|---------------------|---------------------|
| <b>Body (L x W)</b>                    | 18'0" x 8'4"        | 22'0" x 8'4"        | 26'0" x 8'4"        |
| <b>Overall (L x W x H)</b>             | 20'0" x 8'6" x 8'3" | 24'0" x 8'6" x 8'3" | 28'0" x 8'6" x 8'3" |
| <b>Interior (L x W x H)</b>            | 17'9" x 8'1" x 6'6" | 21'9" x 8'1" x 6'6" | 25'9" x 8'1" x 6'6" |
| <b>Platform Height</b>                 | 20"                 | 20"                 | 20"                 |
| <b>Width Between Wheel Boxes</b>       | 83"                 | 83"                 | 83"                 |
| <b>Side Door</b>                       | 32" Bar Lock        | 32" Bar Lock        | 32" Bar Lock        |
| <b>Rear Ramp Door (W x H)</b>          | 94" x 72"           | 94" x 72"           | 94" x 72"           |
| <b>Axle Quantity</b>                   | Tandem              | Tandem              | Tandem              |
| <b>Brakes with Breakaway Kit</b>       | Electric            | Electric            | Electric            |
| <b>Radial Tire Size</b>                | ST205/75R15         | ST205/75R15         | ST205/75R15         |
| <b>Tire Load Range</b>                 | C                   | C                   | C                   |
| <b>Hitch Ball Size</b>                 | 2-5/16"             | 2-5/16"             | 2-5/16"             |
| <b>Hitch Height to Top of Ball</b>     | 19"                 | 19"                 | 19"                 |
| <b>Hitch Weight (% of curb weight)</b> | 10% to 15%          | 10% to 15%          | 10% to 15%          |
| <b>Curb Weight (Approx.)</b>           | 2,485 lbs.          | 2,975 lbs.          | 3,465 lbs.          |
| <b>GVWR</b>                            | 7,000 lbs.          | 7,000 lbs.          | 7,000 lbs.          |
| <b>Payload Capacity (Approx.)</b>      | 4,515 lbs.          | 4,025 lbs.          | 3,535 lbs.          |
| <b>Tube Main Rails</b>                 | 2" x 6"             | 2" x 6"             | 2" x 6"             |
| <b>12v Connector</b>                   | 7-Way               | 7-Way               | 7-Way               |

## STANDARD FEATURES

- Flat Roof/V-Nose Profile
- 16" OC Tube Vertical Wall Posts
- 16" OC Floor Crossmembers
- 24" OC Tube Roof Bows
- Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit
- Chassis Undercoated
- Safety Chains to D.O.T Standards
- 15" Radial Tires with Silver Mod Wheels
- Smooth Aluminum Radius Fenderettes
- 1-Piece Seamless Aluminum Roof
- .080 Aluminum Composite Panels (Select Colors)
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist
- 16" Ramp Extension
- 32" Side Door with Bar Lock
- 12v LED Exterior Lighting
- 12v LED Slim Line Tail Lights
- 12v LED Dome Light with Self Switch
- 3/4" High Performance PlexCore™ Interior Floor
- 3/8" High Performance PlexCore™ Sidewall Liner
- 500 lb. Surface Wall Mounted Rope-Rings (4)
- Semi-Screwless (Screws on Seams only)
- 1-Year Limited Warranty



Standard Features — Semi-Screwless .080 ACP



Standard Interior

