



**AMERICAN
HAULER**

HAULING THE AMERICAN SPIRIT

PREMIUM RACE GOOSENECK

THE SILVER HAWK



WIN BEFORE YOU TAKE THE GREEN

We believe the **SILVER HAWK GOOSENECK** sets the standard for what a car hauler should be. **Balanced for control, built for confidence, and engineered for impact**, this gooseneck commands respect before it ever reaches the track. From the hitch forward to the ramp door back, every surface is designed to protect, built to endure, and styled to impress. The features are substantial, the stance is unmistakable, and the message is clear. With an American Hauler® **SILVER HAWK GOOSENECK** in tow, you don't just arrive ready, you arrive ahead. Proudly built in the USA.

Trailers shown may feature optional equipment available at an additional charge.

SPECIFICATIONS

		SILG8528T4	SILG8532T4	SILG8536T4	SILG8540R4	SILG8544R4
Body:	Length Width	28'0" 8'4"	32'0" 8'4"	36'0" 8'4"	40'0" 8'4"	44'0" 8'4"
Overall:	Length Width Height (to top of roof vent)	28'0" 8'6" 9'2"	32'0" 8'6" 9'2"	36'0" 8'6" 9'2"	40'0" 8'6" 9'2"	44'0" 8'6" 9'2"
Interior:	Width	8'0"	8'0"	8'0"	8'0"	8'0"
Interior:	Length - Lower Deck Length - Upper Deck	19'9" 8'0"	23'9" 8'0"	27'9" 8'0"	31'9" 8'0"	35'9" 8'0"
Interior:	Height - Lower Deck Height - Upper Deck	6'10" 31"	6'10" 31"	6'10" 31"	6'10" 31"	6'10" 31"
Width Between Wheel Boxes		83"	83"	83"	83"	83"
Height of Wheel Box from Floor		9-3/4"	9-3/4"	9-3/4"	9-3/4"	9-3/4"
Platform Height at Beavertail		21"	21"	21"	21"	21"
Torflex® Suspension E-Z Lube® Axles: Qty		Tandem	Tandem	Tandem	Triple	Triple
Electric Brakes with Breakaway Kit		Electric Drum	Electric Drum	Electric Drum	Electric Drum	Electric Drum
Radial Tire Size Tire Load Range		ST235/85R16 E	ST235/85R16 E	ST235/85R16 E	ST235/85R16 E	ST235/85R16 E
Gooseneck Ground Clearance (Approximate)		~ 64"	~ 64"	~ 64"	~ 64"	~ 64"
Hitch Height to Top of Ball (Approximate)		~ 41"	~ 41"	~ 41"	~ 41"	~ 41"
GVWR		12,000 lb.	12,000 lb.	14,000 lb.	18,000 lb.	18,000 lb.
Curb Weight		5,520 lb.	6,020 lb.	6,520 lb.	9,300 lb.	10,025 lb.
Payload Capacity		6,480 lb.	5,980 lb.	5,480 lb.	8,700 lb.	7,975 lb.
Rear Ramp Door Opening - Width x Height		96" x 78"	96" x 78"	96" x 78"	96" x 78"	96" x 78"
12v Male Connection		7-way	7-way	7-way	7-way	7-way
Tube Main Rails		3" x 8"	3" x 8"	3" x 8"	3" x 8"	3" x 8"

STANDARD FEATURES

- 2⁵/₁₆" Adjustable Round Gooseneck Ball Coupler — 25,000 lb.
- .080 ACP Panels, Bonded for Smooth Appearance (Select Colors)
- Cast Aluminum Corners (Front & Rear)
- Stainless Steel Cap and Front Corners
- Polished Aluminum Rear Corners & Header
- 5,000 lb. Square D-Rings with Welded Plates (4)
- Spring-Assisted Rear Ramp Door with Ramp Extension
- Heavy-Duty Locking Paddle Latch on Rear Ramp Door
- Economy Line Ceiling Liner
- 3/4" PlexCore Decking
- 3/8" PlexCore Sidewall Liner
- Dust-Resistant Frame Design
- Vertical Tube Posts 16" On Center
- Spread Torflex® Axles with Drop Skirting
- Goodyear® Radial Tires with Black Aluminum Wheels
- LED Amber Clearance Front 3 Light Center Cluster
- Angled ATP Stoneguard & Enclosed Gooseneck Underbelly
- 36" x 78" Side Entry Door with Recessed Step
- 14" x 14" Non-Powered Roof Vent (2)
- Breakaway Assembly Kit with Charger
- 12V Dome Lights (4)
- LED Exterior Lighting with Smoked Lens
- Beavertail — Length Varies by model
- 8' Upper Deck
- Double Leg Manual 2 Speed Landing Gear
- 3-Year Limited Warranty



Silver Hawk images above shown with optional Turbo Package with Landing Strip In-Floor Lighting

