



**AMERICAN
HAULER**

HAULING THE AMERICAN SPIRIT

CONSUMER-GRADE TRAILERS

THE ARROW DELUXE



DELUXE FEATURES AT AN UNBEATABLE VALUE!

The American Hauler **ARROW DELUXE** is the entry-level trailer you know, built with the popular features you love. It delivers dependable, low-maintenance performance while offering many of the premium upgrades typically found on higher-end models. Designed for durability and versatility, the **ARROW DELUXE** is ready to handle a wide range of hauling needs with confidence. Whether you're transporting equipment, vehicles, or personal belongings, you can rely on it to keep your cargo safe, secure, and protected every mile of the journey.

SPECIFICATIONS

	AR58SA-D	AR610SA-D	AR612SA-D	AR714TA2-D	AR716TA2-D
Body (L x W)	9'4" x 5'0"	11'4" x 6'0"	13'4" x 6'0"	15'4" x 7'0"	17'4" x 7'0"
Overall (L x W x H)	11'4" x 6'8" x 7'1"	14'0" x 7'8" x 8'1"	16'0" x 7'8" x 8'1"	18'0" x 8'6" x 8'2"	20'0" x 8'6" x 8'2"
Interior (L x W x H)	9'1" x 4'9" x 5'6"	11'1" x 5'9" x 6'6"	13'1" x 5'9" x 6'6"	15'1" x 6'9" x 6'6"	17'1" x 6'9" x 6'6"
Platform Height	17"	17"	17"	18"	18"
Side Door	N/A	32" Bar Lock	32" Bar Lock	32" Bar Lock	32" Bar Lock
Rear Door W x H	Single Swing 54" x 60"	Ramp 66" x 72"	Ramp 66" x 72"	Ramp 78" x 72"	Ramp 78" x 72"
Axle Quantity	Single	Single	Single	Tandem	Tandem
Brakes with Breakaway Kit	N/A	Optional	Optional	Electric	Electric
Radial Tire Size	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15	ST205/75R15
Tire Load Range	C	C	C	C	C
Hitch Ball Size	2"	2"	2"	2-5/16"	2-5/16"
Hitch Height to Top of Ball	16"	16"	16"	17"	17"
Hitch Weight (% of curb weight)	10-15%	10-15%	10-15%	10-15%	10-15%
Curb Weight (Approx.)	900 lbs.	1,220 lbs.	1,285 lbs.	2,260 lbs.	2,420 lbs.
GVWR	2,990 lbs.	2,990 lbs.	2,990 lbs.	7,000 lbs.	7,000 lbs.
Payload Capacity (Approx.)	2,090 lbs.	1,770 lbs.	1,705 lbs.	4,740 lbs.	4,580 lbs.
Tube Main Rails	2" x 3"	2" x 3"	2" x 3"	2" x 4"	2" x 4"
12v Connector	4-Way	4-Way	4-Way	7-Way	7-Way

STANDARD FEATURES

- Flat Roof with Sharp V-Nose Profile
- ATP Nose Trim
- 16" OC Tube Vertical Posts
- 16" OC C-Channel Crossmembers
- 24" OC Tube Roof Bows
- Dexter® Spring Axles with 4" Drop
- E-Z Lube® Hubs
- Electric Brakes with Breakaway Kit *(Tandem Axle Models Only)*
- Chassis Undercoated
- Ball Coupler Hitch
- Safety Chains to D.O.T Standards
- 15" Radial Tires with Silver or Black Mod Wheels
- Smooth Aluminum Radius Fenders
- 1-Piece Seamless Aluminum Roof
- .080 Aluminum Composite Panels *(Select Colors)*
- Screwless Exterior *(Bonded Seams)*
- 16" Starbright Stoneguard
- Flow-Thru Sidewall Vents
- Rear Ramp Door with Spring Assist *(Single Swing Door on 5'W Models)*
- 16" Ramp Extension
- 32" Side Door with Flush Lock *(No Side Door on 5'W Models)*
- 12v LED Exterior Lighting *(Featuring Exclusive LazerMax design)*
- 12v LED Slim Line Tail Lights
- 12v LED Dome Light with Self-Switch
- 3/4" High Performance PlexCore™ Interior Floor
- 3/8" High Performance PlexCore™ Sidewall Liner
- (4) 5,000 lb. Floor D-Rings with Steel Backer Plate *(500 lb. Wall Rope Rings on 5'W models)*
- 1-Year Limited Warranty

**Phantom Package available at additional cost on select models*



6' x 12' Arrow Deluxe



Arrow Deluxe Interior

